

American National Standard

Adopted for Use by
the Federal Government



FIPS PUB 13
See Notice on Inside
Front Cover

rectangular holes in twelve-row punched cards



american national standards institute, inc.
1430 broadway, new york, new york 10018

This standard was approved as a Federal Information Processing Standard by the Office of Management and Budget on June 16, 1971.

Details concerning the use of this standard within the Federal Government are contained in FIPS PUB 13, RECTANGULAR HOLES IN TWELVE-ROW PUNCHED CARDS. For a complete list of the publications available in the FEDERAL INFORMATION PROCESSING STANDARDS Series, write to the Office of Technical Information and Publications, National Bureau of Standards, Washington, D.C. 20234.

American National Standard Rectangular Holes in Twelve-Row Punched Cards

American National Standard

This standard is one of more than 4000 approved as either a USA Standard or as an American Standard. It became an American National Standard in October 1969 when the Institute changed its name to American National Standards Institute, Inc.

ANSI, 1430 Broadway, New York, N.Y. 10018

Sponsor
Business Equipment Manufacturers Association

Approved October 27, 1967
United States of America Standards Institute

American National Standard

An American National Standard implies a consensus of those substantially concerned with its scope and provisions. An American National Standard is intended as a guide to aid the manufacturer, the consumer, and the general public. The existence of an American National Standard does not in any respect preclude anyone, whether he has approved the standard or not, from manufacturing, marketing, purchasing, or using products, processes, or procedures not conforming to the standard. American National Standards are subject to periodic review and users are cautioned to obtain the latest editions.

CAUTION NOTICE: This American National Standard may be revised or withdrawn at any time. The procedures of the American National Standards Institute require that action be taken to reaffirm, revise, or withdraw this standard no later than five years from the date of publication. Purchasers of American National Standards may receive current information on all standards by calling or writing the American National Standards Institute.

Published by

American National Standards Institute, Inc
1430 Broadway, New York, New York 10018

Copyright 1967 by the United States of America Standards Institute
Universal Decimal Classification 681.177:681.3

No portion of this publication may be quoted or reproduced in any form without the written permission of the American National Standards Institute.

Printed in USA

Foreword

(This Foreword is not a part of the USA Standard Rectangular Holes in Twelve-Row Punched Cards, X3.21-1967.)

This publication is one of a series of standards relating to information interchange between information processing systems, communications systems, and associated equipment through the medium of punched paper cards. This standard specifies the size and locations of rectangular holes in twelve-row, 3¼ inch wide punched cards.

A related standard, X3.11-1966 specifies the dimensions, quality of paper, and test methods of 7⅞ inch length cards for information processing.

This standard was developed by a group of highly qualified and experienced punched-card specialists representing manufacturers and users of card stock, cards, and card processing equipment. Adherence to this standard will eliminate many misunderstandings.

Suggestions for improvement gained in the use of this standard will be welcome. They should be sent to the United States of America Standards Institute, 10 East 40th Street, New York, N.Y. 10016.

The USA Standards Committee on Computers and Information Processing, X3, had the following personnel at the time it processed and approved this standard.

C. A. Phillips, *Chairman*

P. B. Goodstat, *Secretary*

Organization Represented

Administrative Management Society
Air Transport Association
American Bankers Association
American Gas Association
American Newspaper Publishers Association
American Petroleum Institute
Association of American Railroads
Association for Computing Machinery
Business Equipment Manufacturers Association

Data Processing Management Association
Edison Electric Institute
Electronic Industries Association
Engineers Joint Council
General Services Administration
Institute of Electrical and Electronics Engineers
Insurance Accounting and Statistical Association
International Communications Association
Joint Users Group
Life Office Management Association
National Bureau of Standards
National Machine Tool Builders Association
National Retail Merchants Association
Scientific Apparatus Makers Association
Systems and Procedures Association
Telephone Group
USA Standards Committee on Office Machinery, X4
U. S. Department of Defense

Name of Representative

C. S. Everhardt
F. C. White
G. W. Frey
E. A. Cotty
W. D. Rinehart
F. A. Gitzendanner
R. A. Petrash
D. T. Ross
R. Bemmer
W. H. Burkhart
R. F. Clippinger
C. T. Deere
U. C. S. Dilks
S. Erdreich
I. M. Gardoff
R. W. Green
J. A. Haddad
R. J. Mindlin
G. Poorte
D. J. Reven
R. C. Elliott
H. D. Limmer
H. H. Smith
W. M. Carlson
M. W. Burris
G. W. Patterson
W. Bregartner
C. L. Hutchinson
R. E. Utman
E. Boulanger
J. H. Wegstein
E. Koschella
E. Langtry
W. B. Schultz
E. Tomeski
L. W. Claussen
C. E. Ginder
G. L. Bowlby

The X3.2 Subcommittee had the following personnel at the time it processed and approved this standard:

L. L. Griffin, *Chairman*

R. Adams
J. F. Auwaerter
E. A. Avakian
T. R. Bousquet
R. M. Brown
N. Clark
C. Crandall
R. J. Donahue
S. Erdreich
D. E. Holmes
H. R. Hoots
R. M. Ireland
M. R. Jepson

D. A. Kerr
R. Kudisch
J. L. Little
C. E. Mackenzie
W. H. McKenzie
M. Mendelsohn
G. L. Murphy
J. K. Nelson
H. Spielman
James E. Taunt
R. E. Utman
E. F. Vidro, Jr
G. E. Williams

The Physical Standards Group of the X3.2.3 Task Group on Punched Cards developed this standard and had the following personnel:

H. J. Bode
R. M. Brown
R. N. Eichorn
T. R. Evans
R. H. Hunter

P. A. Schenk

J. J. Krause
N. Locke
C. E. Mackenzie
R. J. Ridolfi
F. M. Schaller

Contents

SECTION	PAGE
1. Scope	7
2. Detail Requirements	7
2.1 Size	7
2.2 Location	7
2.3 Environment	7
Fig. 1	7
Appendix Environmental Considerations	8
A1. Cardstock Dimensional Instability	8
A1.1 Variation of Card Dimensions	8
A1.2 Variation in Hole Locations	8
A1.3 Additional Information	8
A2. User Responsibility	8

American National Standard Rectangular Holes in Twelve-Row Punched Cards

1. Scope

This standard specifies the size and location of rectangular holes in twelve-row $3\frac{1}{4}$ -inch wide punched cards. To be a processable document, suitable for information interchange, cards must also meet USA Standard Specifications for General Purpose Paper Cards for Information Processing, X3.11-1966.

2. Detail Requirements (See Fig. 1)

2.1 Size. All edges of the hole shall fall between two concentric rectangles whose edges

are parallel to the X and Y datum lines. (See 2.2.1.1 and 2.2.2.1.)¹ The rectangles are dimensioned as follows:

Outer

height: 0.126 inch
length: 0.056 inch

Inner

height: 0.124 inch
length: 0.054 inch

2.2 Location. All holes shall nominally center on the intersection of longitudinal and transverse grid lines located as in the following.

2.2.1 Longitudinal Grid Lines. Twelve longitudinal grid lines (rows) shall be spaced at increments of 0.250 inch from the X datum line.

2.2.1.1 X Datum Line—A horizontal line lying along the top edge of the card.

2.2.2 Transverse Grid Lines. Transverse grid lines (columns) shall be spaced at increments of 0.087 inch from a transverse grid line spaced 0.251 inch from the Y datum line.

2.2.2.1 Y Datum Line—A vertical line exactly at right angles to the X datum line and intersecting the mid-point of the right edge of the card.


2.2.3 Tolerance on Hole Location.

2.2.3.1 Reading Tolerance—The centerline of each hole shall be within 0.018 inch of their corresponding longitudinal and transverse grid lines at the time of reading.

2.2.3.2 Punching Tolerance—Because changes in environment affect the dimensions of paper cards (see Appendix), the centerlines of each hole should be within 0.010 inch of their corresponding longitudinal and transverse grid lines at the time of punching.

2.3 Environments. Environment is not specified in this standard but should be agreed upon by those responsible for punching, reading, transporting, and storing cards.

Fig. 1



All dimensions are in inches.

NOTES:

(1) Y - Y is perpendicular to X - X and intersects the mid-point of right edge of card.

(2) Vertical centerline of holes may vary ± 0.010 from Y - Y at time of punching (see 2.2.3.2) and ± 0.018 at time of reading.

(3) Horizontal centerline of holes may vary ± 0.010 from X - X at time of punching (see 2.2.3.2) and ± 0.018 at time of reading.

Appendix

(This Appendix is not a part of the USA Standard Rectangular Holes in Twelve-Row Punched Cards, X3.21-1967, but is included to facilitate its use.)

Environmental Considerations

A1. Cardstock Dimensional Instability

Cardstock used for punched cards is inherently subject to changes in dimensions with changes in environmental conditions, particularly changes in relative humidity (RH).

A1.1 Variation of Card Dimensions. At a constant temperature of 73°F, a change in relative humidity from 20 percent to 75 percent, or from 75 percent to 20 percent, will change the dimensions of the card as much as 0.018 inch in length and 0.023 inch in width.

Temperature variations within ranges normally maintained for human comfort will not substantially affect dimensional changes as stated above.

A1.2 Variation in Hole Location. The location of punched holes will vary in accordance with the above variations in card dimensions.

A1.3 Additional Information. For additional information, see the Appendix to the USA Standard Specifications for General Purpose Paper Cards for Information Processing, X3.11-1966.

A2. User Responsibility

The users of card equipment must accept the responsibility for maintaining the proper environment to assure reliable information interchange.

Maximum reliability of information interchange will result when cards are punched, read, transported, and stored at the same temperature and RH levels. Excursions in RH in excess of 20 percent should be avoided after the cards are punched. Cards exposed to above 75-percent RH undergo dimensional changes, some of which, due to relaxation of paper fiber stresses, may not be reversible when the cards are reconditioned to below 75-percent RH.

American National Standards on Computers and Information Processing

X3.1-1969 Synchronous Signaling Rates for Data Transmission

X3.2-1970 Print Specifications for Magnetic Ink Character Recognition

X3.3-1970 Bank Check Specifications for Magnetic Ink Character Recognition

X3.4-1968 Code for Information Interchange

X3.5-1970 Flowchart Symbols and Their Usage in Information Processing

X3.6-1965 Perforated Tape Code for Information Interchange

X3.9-1966 FORTRAN

X3.10-1966 Basic FORTRAN

X3.11-1969 Specifications for General Purpose Paper Cards for Information Processing

X3.12-1970 Vocabulary for Information Processing

X3.14-1973 Recorded Magnetic Tape for Information Interchange (200 CPI, NRZI)

X3.15-1966 Bit Sequencing of the American National Standard Code for Information Interchange in Serial-by-Bit Data Transmission

X3.16-1966 Character Structure and Character Parity Sense for Serial-by-Bit Data Communication in the American National Standard Code for Information Interchange

X3.17-1966 Character Set for Optical Character Recognition

X3.18-1967 One-Inch Perforated Paper Tape for Information Interchange

X3.19-1967 Eleven-Sixteenths Inch Perforated Paper Tape for Information Interchange

X3.20-1967 Take-Up Reels for One-Inch Perforated Tape for Information Interchange

X3.21-1967 Rectangular Holes in Twelve-Row Punched Cards

X3.22-1973 Recorded Magnetic Tape for Information Interchange (800 CPI, NRZI)

X3.23-1968 COBOL

X3.24-1968 Signal Quality at Interface Between Data Processing Terminal Equipment and Synchronous Data Communication Equipment for Serial Data Transmission

X3.25-1968 Character Structure and Character Parity Sense for Parallel-by-Bit Communication in the American National Standard Code for Information Interchange

X3.26-1970 Hollerith Punched Card Code

X3.27-1969 Magnetic Tape Labels for Information Interchange

X3.28-1971 Procedures for the Use of the Communication Control Characters of American National Standard Code for Information Interchange in Specified Data Communication Links

X3.29-1971 Specifications for Properties of Unpunched Oiled Paper Perforator Tape

X3.30-1971 Representation for Calendar Date and Ordinal Date for Information Interchange

X3.31-1973 Structure for the Identification of the Counties of the United States for Information Interchange

X3.34-1972 Interchange Rolls of Perforated Tape for Information Interchange

X3.38-1972 Identification of States of the United States (Including the District of Columbia) for Information Interchange

X3.39-1973 Recorded Magnetic Tape for Information Interchange (1600 CPI, PE)

X3.40-1973 Unrecorded Magnetic Tape for Information Interchange (9-Track 200 and 800 CPI, NRZI, and 1600 CPI, PE)

For a free and complete list of all American National Standards, write:

American National Standards Institute, Inc
1430 Broadway
New York, N.Y. 10018